

DERWENT-ACC- 1985-317400**NO:****DERWENT-** 198551**WEEK:**

COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Gas producer jacket - with through pins and shorter pins
between inner and outer shells**INVENTOR:** BERGER, F; FEDOTOV, V ; GUDYMOV, E ; LUCAS, K ; SCHINGNITZ,
M ; SEMENOV, V**PATENT-** BRENNSTOFF FREIBERG[FREI] , BRENNSTOFFINST FREIBERG
ASSIGNEE: [FREI]**PRIORITY-DATA:** 1984DD-0266957 (September 4, 1984)**PATENT-FAMILY:**

PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
DD 226588 A	August 28, 1985	N/A	011	N/A
CS 8505319 A	December 18, 1986	N/A	000	N/A
DE 3523610 A	March 13, 1986	N/A	000	N/A
<u>FR 2569827</u> A	March 7, 1986	N/A	000	N/A
JP 61066793 A	April 5, 1986	N/A	000	N/A

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO	APPL-DATE
DE 3523610A	N/A	1986DE-3523610	March 13, 1986
JP 61066793A	N/A	1985JP-0194013	September 4, 1985

INT-CL (IPC): C10J003/48, F23J013/00 , F23M005/08**ABSTRACTED-PUB-NO:** DD 226588A**BASIC-ABSTRACT:**

A pinned sheath for e.g. a gas producer with liq. slag extraction to act as a cooling jacket consists of parallel plane discs, cylindrical shell rings and connecting conical sections. The inner shells are joined to the outer shells by spacer pins. Additional shorter pins are welded to the inner shells and protrude into the cooling jacket.

ADVANTAGE - The better cooling effect permits the temp. in the

reaction zone to be raised by 300-500 deg. C. The pins break up any formed steam bubbles and result in a higher functional reliability of the gas producer.

CHOSEN- Dwg.0/2

DRAWING:

TITLE-TERMS: GAS PRODUCE JACKET THROUGH PIN SHORT PIN INNER OUTER SHELL

DERWENT-CLASS: H09 Q73

CPI-CODES: H09-C;

SECONDARY-ACC-NO:

CPI Secondary Accession Numbers: C1985-137130

PUB-NO: FR002569827A1
DOCUMENT-IDENTIFIER: FR 2569827 A1
TITLE: TITLE DATA NOT AVAILABLE
PUBN-DATE: March 7, 1986

INVENTOR-INFORMATION:

NAME	COUNTRY
GUDYMOV, ERNEST	N/A
SEMENTOV, VLADIMIR	N/A
FEDOTOV, VASILIJ	N/A
LUCAS, KLAUS	N/A
BERGER, FRIEDRICH	N/A
SCHINGNITZ, MANFRED	N/A

ASSIGNEE-INFORMATION:

NAME	COUNTRY
FREIBERG BRENNSTOFFINST	DD

APPL-NO: FR08510409
APPL-DATE: July 8, 1985

PRIORITY-DATA: DD26695784A (September 4, 1984)

INT-CL (IPC): C10J003/48

EUR-CL (EPC): C10J003/48

US-CL-CURRENT: 48/62R, 89/196

ABSTRACT:

A pinned sheath for e.g. a gas producer with liq. slag extraction to act as a cooling jacket consists of parallel plane discs, cylindrical shell rings and connecting conical sections. The inner shells are joined to the outer shells by spacer pins. Additional shorter pins are welded to the inner shells and protrude into the cooling jacket.